CDLC0103

# USED WITH: CAN BUCKLING TESTERS



**CHANGE PARTS** 

9800 9820

LATEST VERSION(S) MAY VARY SLIGHTLY FROM PHOTO(S)

FOR DIRECT TECHNICAL ASSISTANCE USE FAX # (860) 496-0255

## **PRODUCT OVERVIEW**

These Change Parts are used with can buckle testers to hold a sample in place as it is being pressurized with air. The Change Parts are manufactured by Altek to specific customer requirements.

#### 9800 DESCRIPTION

The 9800 Change Part holds a necked-in can in place as it is being pressurized. The 9800 consists of a displacement plug over which the can is placed; an optional plug extender for use with a second height of can; and a pair of jaws which clamp the sample in place against the displacement plug during testing.

#### 9820 DESCRIPTION

The 9820 Change Part holds a straight wall can in place as it is being pressurized. The 9820 consists of a displacement plug over which the can is placed; an optional plug extender for use with a second height of can; a pair of jaws which clamp the sample in place against the displacement plug during testing and a seal assembly.

## SPECIFICATIONS

The following document describes the specifications for these Change Parts:

CDXC0101 - Change Parts Specifications

#### 9800 ORDERING

The 9800 is ordered by specifying 9800, the can straight wall diameter, the can necked-in diameter, the can height, and the second height (if applicable). Examples:

9800: 211 - 207.5 x 413 (SW dia, NI dia, hgt; 207.5 = double-necked)

9800: 211 - 206 x 413 x 604 (SW dia, NI dia, hgt, second hgt; 206=triple-necked)

#### 9820 ORDERING

The 9820 is ordered by specifying 9820, the can straight wall diameter, the can height, and second height (if applicable). Samples MUST be provided to ensure proper manufacture of the 9820 Change Parts. Example:

9820: 211 x 413 (SW dia, hgt)

## TECHNICAL SUPPORT

Altek provides comprehensive technical support to its customers worldwide. For assistance, contact Altek and ask for the Engineering department.

#### REPAIR

Altek customers can obtain a return authorization from Altek and ship a faulty unit in for repair, if necessary. In addition, replacement parts for all models are available from Altek.

#### WARRANTY

All Altek products are built to the highest standards of quality and reliability. This Altek product is backed by a full 90-day warranty.

## FURTHER INFORMATION

See the accompanying specifications for additional information concerning this product. If specifications were not included with this flier, please call Altek; they will be mailed or faxed as quickly as possible

## CUSTOM DESIGN.

Altek can custom design inspection and test equipment to meet specific customer requirements. Custom Change Parts can also be designed and manufactured for most Altek products; contact Altek for further information.

## A NOTE ON SAMPLES

Samples sent to Altek as a requirement for the manufacture of Change Parts must be submitted in their "as tested" form. For instance, if an end will be tested unseamed on a piece of test equipment, Altek must receive ends that are unseamed in order to properly manufacture the Change Parts. Contact Altek for further information regarding sample requirements for Change Parts manufacture.

For more information, contact Altek between 8:00 am and 5:00 pm ET, Monday thru Friday. The Altek company address and phone numbers can be found on the front of this flier.

## ORDERING INFORMATION

To purchase this product:

This flier is supplemented by additional literature in the form of a specification sheet.

At least one of these Change Parts sets is required for operation of a 9009B1, 9009C\_, 9009F2 series Altek buckle tester.

Customer samples are required in order to ensure proper manufacture and operation of these Change Parts.

These Change Parts are ordered by specifying the required information (as described above).

\yC01 SPECIFICATIONS

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

CHANGE PARTS: ..... 9800, 9820

USED WITH MODELS: ..... 9009B1, 9009C2, 9009C5, 9009F2

EFFECTIVE DATE: ..... DEC 17, 1994

SAMPLE TYPE: ..... BEVERAGE CANS

NOTE: A SEPARATE SET OF CHANGE PARTS MUST BE MANUFACTURED FOR EACH SPECIFIC DIAMETER OR CROSS-SECTION OF SAMPLE.

9800:	For round, necked-in, oper	n metal beverage cans
	Can Neck Diameter	200 - 300 (2" to 3")
	Can Height	
9820:	For round, straight wall,	open metal beverage cans
	Can Body Diameter	202 - 307 (2 1/8" to 3 7/16")
	Can Height	